

## ADVANCE CURE AND SEAL 25

### DESCRIPTION

The philosophy of Cornerstone Coatings has always been “to make a better product” than what is currently available in the marketplace. Cornerstone Coatings has done this by incorporating “slow dry technology” in all of our VOC compliant solvent based acrylics. This slow dry technology allows Cornerstone Coatings to lead the way in the industry by providing the easiest products to use in the Canadian market. The applicator is able to use Advance Cure and Seal during the day in temperatures up to 27 C.

### FEATURES

- ~Meets ASTM C309
- ~Can be used during the day
- ~Cure and Seal in 1 coat
- ~VOC Compliant – 350 g/l
- ~Superior Interior and Exterior Durability
- ~Increased Gloss Retention
- ~Will not leave a milky film
- ~UV Stable and Non-Yellowing

### USES

All Horizontal Concrete/Stamped Concrete/Stained Concrete/Stenciled Concrete/Paving Stones/Exposed Aggregate Surfaces/Block Walls/Power Trowel and Broom Finish Concrete

### PHYSICAL CHARACTERISTICS

VOC'S: 350 grams/litre  
Meets ASTM C309  
Recommended Coats: cure – 1  
Coverage: Approximately 250 sq.ft/gal  
Drytime: 1 - 2 hours at 77 F or 25 C  
Clean-up: Xylene  
Color: Water Clear  
Flashpoint: 4.4 C  
Exterior Durability: Excellent  
Wearing Quality: Excellent  
Solids: 25% Equivalent  
Shelf Life: 3 yrs in original unopened container

### PACKAGING

Packaging: 18.9 Litre Pail  
205 Litre Drum

### CAUTIONS

Do not use Advance Cure and Seal in combination with any other acrylic sealer or cure and seal except Cornerstone Coatings solvent based Acrylics.

### SURFACE PREPARATION

Area to be sealed must be cleaned and free of all foreign matter such as dirt, rubber marks, paint etc.

### APPLICATION

Apply Advance Cure and Seal immediately after all the surface water has disappeared and the surface can be walked on without marring. Applying the product too early or too late can affect the overall curing performance. Apply with a solvent resistant lint-free long nap roller or spray. Apply uniformly at 250 square feet/gallon.

### LIMITATIONS

This product should not be used at temperatures below 40F (4C). Avoid spraying Advance Cure and Seal into joint prior to installation of sealant. Do Not apply concrete or mortar toppings over sealed surfaces. May show rubber tire marks.

### WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.