

## » *Liquid Poly:*

### > HIGHLIGHTS

- *Easy to Use*
- *Cuts down on preparation time*
- *Can be applied in hot or cold weather*
- *Enables easy removal of concrete splatter*
- *Can be Rolled, Sprayed, or Brushed*
- *Does not require any degreasers*
- *Stops concrete staining*
- *VOC Compliant: <30g per Litre*
- *Water-based*
- *Environmentally Safe*
- *1 coat application in most cases*
- *Use cold water to remove*

### > *Removal Instructions:*

Use a pressure washer and cold water. Wet down an area 40-50 feet long, this allows the Liquid Poly to start softening, then pressure wash Liquid Poly off.

### > *Application Instructions:*

Use an industrial pump sprayer to apply Liquid Poly. Recommended tip size is .5gpm. Apply evenly from the bottom up with good product coverage at a rate of approximately 250 square feet per gallon. Concrete can splatter up to 8 feet high, so apply Liquid Poly up to that height.

It is very important to saturate the area with Liquid Poly that is to be protected from concrete splatter. If you do this right, it is a dream to remove. If in doubt, a second coat of Liquid Poly will ensure proper coverage.

### > *Does not contain any:*

*Wax, Soy, Mineral Oils, or Silicone.*

### > *Description:*

Liquid Poly is a water-based temporary protective coating that forms a membrane to protect the surface from concrete splatter and staining.

During concrete pumping and placing/finishing operations, concrete is typically splattered on the surrounding areas. This is a major problem, because the concrete is not easily removed after it dries, and can often stain, leaving the area unsightly.

Liquid Poly is easily removed with a pressure washer using cold water. The coating will easily soften and melt, and the concrete splatter washes away easily without leaving concrete stains. Concrete can be painted after thoroughly removing the Liquid Poly.

### > *Uses:*

Liquid Poly can be used on a wide variety of surfaces such as: glass, faced metal building insulation, insulated metal wall panels, pre-painted metal wall panels, structural steel, wood, stamped concrete, cindercrete blocks, and pre-cast concrete, acrylic stucco, parging, tools and equipment.

### > *Cautions:*

- *Do Not Freeze product.*
- *We recommend testing a small area to observe possible adverse reactions before applying.*
- *Apply at suitable application rates.*

### > *Manufacturers Warranty:*

We warrant our products to be of good quality and will replace any products proven defective. The user shall determine the suitability of the product for the intended use, and assume all risks and liability of the application and use of the product. Akkeri products does not make any warranties or guarantees of product fitness for a particular purpose or merchantability. This warranty super-cedes all other warranties express or implied.