

AQUATEK

Waterbased High Sheen Sealer

AQUATEK is one of the most advanced formulation water-based acrylic sealers in the market. Aquatek was designed to create a high gloss finish with excellent exterior durability properties. Aquatek is easily applied with a brush and roller, or sprayer. It has no harsh smell, and dries quickly. Aquatek goes on white for ease of application and dries clear.

ADVANTAGES

*Meets **LEED Requirements**.

* Seals and Dust-proofs Concrete

*High Gloss Finish

*Excellent Resistance to Water blushing

*Non-Yellowing and UV Stable

* Low VOC content - 70 grams/litre

* Excellent Stain Resistance

* Excellent Adhesion

* Very Good Abrasion Resistance

* Good Chemical Resistance

* Excellent Anti-spalling Material

* Solvent Free

* Dries Quickly

* Ready to Use

USES

- Broom Finish and Power Trowel Concrete, Stamped Concrete, Exposed Aggregate, Acid Stained Concrete, and Overlays
- Horizontal or Vertical concrete surfaces
- Interior or Exterior

PHYSICAL CHARACTERISTICS

VOC: ~70 grams/Litre

Sealing Concrete Recommended Coats: 2

Dilution: None, use as supplied

Physical State: Liquid

Color: Pale White

Weight: 8.5 lbs

Skimming: None

Cleaning Equipment: Water

Coverage: 250 sq ft/gal

Food Safe: Approved

Drytime: 30 to 60 minutes 21 C (70 F)

ASTM D-658-44 Abrasion Resistance 250 g/mil

Shelf Life: 1 yr in original unopened container

CAUTIONS

DO NOT FREEZE

DO NOT DILUTE PRODUCT OR ALTER IN ANY WAY.

Do not apply to temperatures below 5 C or 41 F

APPLICATION

- Stir or mix product before use.
- Area to be sealed must be cleaned and free of all foreign matter such as dirt, rubber marks, paint, oil etc.
- Apply at 250 sq. ft. per gallon, on dry surface.
- Apply with spray, brush, or roller. Apply AquaTek uniformly to form a continuous film.
- Minimum of 2 coats required for long-term durability and shine.
- Product goes on white and dries clear.
- Apply second coat 2 -4 hours after first or when dry.
- Roll out any puddles that form.

PACKAGING

1 gallon/ 3.78 litre pails

5 gallon/ 18.9 litre pails

205 Litre Drums

COVERAGE

250 square feet/gallon (depending on porosity of surface)

DRYING TIME

At 21 C (70 F) with 50% R.H.

Dry to touch - 30 to 60 minutes

Re-Coat - 2 to 4 hours

Light foot traffic - 8 hours

Normal traffic - 24 hours

Maximum hardness - 7 days

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.

LAST UPDATED: MAY 6, 2015