

SUPER-GRIP

Super-grip is clear non-slip additive that will take on the color of the sealer and the color of the concrete underneath unlike other materials in the market that leave a white or brown color.

Super-grip is harder than sand and will not crush easily, therefore it doesn't compromise the coating.

The unique light reflecting qualities of Super-grip adds a bit of sparkle to your surface, without changing the color of the coating. Use as much or as little as desired to create the perfect non-slip surface and effect.

Simply broadcast Super-grip onto your wet coating to provide excellent traction to any surface. Super-grip is desirable for any location in which a non-slip surface is required, such as pools, steps, decks or ramps.

Super-grip is available in #15, #17, #20, and #25 sizes. Super-grip is economically priced and available in 3 lb bottles and 50 lb pails. Meets **LEED Requirements**.

HIGHLIGHTS

- Superior traction
- Adds sparkle (reflects light)
- Clear (transparent)
- Economical
- Easy to apply
- VOCs – 0
- Does not discolor decorative concrete

USES

- Non-slip additive for any coating
- Using Super-grip with any clear coating will give the coating sparkle
- Can be used directly on concrete

EPOXY INSTRUCTIONS

Apply the 1st coat of Epoxy. While still wet, broadcast Super-grip evenly over the entire surface. Once dry, apply the 2nd coat of Epoxy.

Or add 1 litre of Super-grip to a 4 litre kit of Epoxy, and mix thoroughly before applying.

ACRYLIC INSTRUCTIONS

Apply first coat of Premium Acrylic. Broadcast Super-grip evenly over entire surface while the acrylic is still wet. Apply a second coat of premium Acrylic once the first coat is dry. This will lock in the Super-grip. Super-grip will take on the color of the concrete and is transparent.

MESH SIZES

Supergrip #30 (20-30)
Supergrip #20 (30-80)
Supergrip #15 (40-50)
Supergrip #17 (70-100)

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.

LAST UPDATED: DECEMBER 19, 2012